Max. Marks:100

USN					CMRIT LIBRARY
					BANGALORE - 569 937

Seventh Semester B.E. Degree Examination, June/July 2018

DSP Algorithms and Architecture

Time: 3 hrs. Note: Answer FIVE full questions, selecting at least TWO questions from each part.

PART - A

- Explain digital signal processing with a neat block diagram. (04 Marks) 1 Explain discrete time sequence in detail. Determine the periods for the periodic sequences,
 - (ii) e (i) e 8

Mention the difference between FIR and IIR filters. Find the magnitude and phase response of an FIR filter represented by the difference equation, y(n) = 0.5x(n) - 0.5x(n-1)

> (08 Marks) (06 Marks)

- How does the barrel shifter in a DSP works? Explain with an example. 2 a.
 - (06 Marks) With a neat block diagram, explain the working of MAC unit.
 - Explain the bit reversed addressing mode for a 16 point FFT with a neat diagram and step by (08 Marks) step generation of binary code.
- Compare architectural features of TMS320C25, DSP56000 and ADSP2100 fixed point DSP. 3 (06 Marks)
 - Explain any five addressing modes of TMS320C54XX with one example each. (10 Marks) b.
 - Identify the addressing modes of the source operand in each of the following instructions: (i) ADD, *AR2+OB, A (ii) ADD *AR2+, A (iii) ADD *AR2+%, A (iv) ADD #23h, A (04 Marks)
- Explain the following assembler directives of TMS320 DSP processor:
 - (iii) .text (ii) .data (i) .mmregs

(04 Marks)

- Write a program to find the sum of series of signed number from address 410H to 41FH (08 Marks) given by $A = \sum dmad$.
- Explain with one example each the four types of classifications of assembly language (08 Marks) instructions of TMS320 DSP processor.

PART - B

- Determine the values respresented by the 16 bit fixed point number $N_1 = 4D00$ and 5 (04 Marks) $N_2 = CDCAH$ in Q7 and Q15 notation.
 - Write an ALP for the FIR filter with 200 input samples using 16 length circular buffers for (10 Marks) the TMS320 DSP.
 - Write an ALP to multiply two Q15 numbers to produce a Q15 result for the TMS320 DSP. (06 Marks)
- Explain scaling operation in DSP processor and derive the expression for optimal scaling (08 Marks) factor for DIT FFT butterfly algorithm.
 - b. Write a pseudo code to determine 8 point DFT using DIT FFT algorithm invoking butterfly (12 Marks) subroutine in a nested loop for each stage.
- Explain the working of DMA with respect to the TMS320 DSP processor. (08 Marks)
 - Explain the working of interrupts in TMS320 DSP. b.

(08 Marks)

Explain the memory space organization of TMS32054XX DSP.

(04 Marks)

- Explain the working of PMC 3002 CODEC with neat block diagram. A PMC 3002 is 8 programmed for 12 kHz sampling rate, determine the divisor N to be written to the CPLD of (08 Marks) the DSK and various clock frequencies.
 - Explain the biotelemetry receiver system with the help of a block diagram. (06 Marks) (06 Marks)
 - Explain with a block diagram clipping auto correlation speech detector.

