TE Fourth Semester B.E. Degree Examination, June/July 2016 ansformers and Induction Machines

Max. Marks:100

Note: Answer FIVE full questions, selecting at least TWO questions from each part.

PART -<u>A</u>

- With neat schematic diagram, explain core and shell type transformer. 1 a.
 - Discuss the working condition of 1-\$\phi\$ transformer on resistive load with vector diagram.
 - A 230/460 volts transformer has a primary resistance of 0.2Ω and a reactance of 0.5Ω and the corresponding values for the secondary are 0.75Ω and 1.8Ω respectively. Find the secondary terminal voltage when supplying i) 10A at 0.8 p.f. lagging; ii) 10A at 0.8 p.f (08 Marks) leading.
- Develop the equivalent of a 1-\phi transformer referred to primary side from the fundamentals. 2
 - Discuss the different types of losses in transformer and derive efficiency of transformer. b. (06 Marks)

A 200 kVA single phase transformer is in circuit continuously. For 8 hours in a day the load is 80 kW at unity power factor and for the remaining period of 24 ours it runs on no-load. Full load copper losses are 3.02 kW and the iron losses are 1.6 kW. Find all day efficiency. (08 Marks)

- Discuss the essential and desirable conditions to be fulfilled for operating two single phase 3 transformers in parallel.
 - What is an auto transformer? State its merits and demerits over two winding transformer. b. (06 Marks)
 - Two transformers have following characteristics:

Transformer 1 — % IR = 1.0% and % IX = 5.0%

Transformer 2 — % IR = 1.5% and % IX = 4.0%

How they will share a load of 100 kVA at 0.8 p.f lagging?

(08 Marks)

- Draw the soft connection of transformer and mark the terminals. Explain its merits and 4 (06 Marks) demerits. (06 Marks)
 - b. Briefly discuss the choice of transformer connections.
 - Give the detail analysis of load sharing between two three phase transformers operating in (08 Marks) parallel.

PART <u>– B</u>

- Bring out clearly, with the help of neat sketches the difference between the 3-phase slip ring 5 induction motor and three phase squirrel cage induction motor. (06 Marks) (06 Marks)
 - Explain the terms slip, slip frequency and give the relation between them. A 746 kW, 3-phase, 50 Hz 16-pole induction motor has a rotor impedance of (0.02 + j0.15)
 - Ω at stand still full-load torque is obtained at 360 rpm. Calculate: i) The ratio of maximum to full-load torque; ii) The speed for maximum torque and iii) The rotor resistance to be (08 Marks) added to get maximum starting torque.

- 6 a. Enumerate various components of power loss in an induction motor and name the parts where in these occur. (06 Marks)
 - b. Draw the circle diagram of a 3-phase mesh connected, 30 h.p, 500V, 4 pole, 50Hz cage type induction motor. The table gives the measurements of line current and voltage and readings of two watt meters connected to measure the input power.

No-load	500V	8.3A	+2.85 kW	-1.35 kW
Blocked rotor test	100 V	32 A	-0.75 kW	+2.35 kW

Find from the diagram for full-load:

- i) Line current
- ii) Power factor
- iii) Efficiency and
- iv) Maximum output.

(14 Marks)

- 7 a. With neat sketch, explain the construction of deep bar cage rotor motor. (06 Marks)
 - b. Draw the torque-speed characteristics double cage rotor motor. How these characteristics are different from squirrel cage induction motor? (06 Marks)
 - c. Describe with a neat diagram the principle of operation of induction generator. (08 Marks)
- 8 a. Why the starter is necessary to start an induction motor? Mention the various methods of starting and discuss the limitations of these methods. (06 Marks)
 - b. With neat schematic diagram, explain the method of star-delta transformer. (06 Marks)
 - c. With neat sketches, explain the construction working principle of
 - i) Split phase and ii) Capacitor start single phase induction motor (08 Marks)

* * * * *