Third Semester B.E. Degree Examination, Dec.2019/Jan.2020 **Mechanics of Materials**


Time: 3 hrs

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

- Define the following terms: 1
 - (i) Stress (ii) Strain
- (iii) Young's Modulus (iv) Poisson's ratio (v) Hooke's law.
- (05 Marks)
- Derive an expression for the total elongation of a tapered circular bar cross section of (05 Marks) diameter 'D' and 'd', when subjected to an axial load 'P'.
- A brass bar having cross sectional area of 1000 mm², is subjected to axial forces shown in Fig. Q1 (c). Find the total elongation of the bar. Take $E = 100 \text{ GN/m}^2$. (10 Marks)



OR


- Draw stress strain diagram for mild-steel and mark all the salient points. (04 Marks)
 - A concrete column of cross sectional area 400mm × 400mm is re-inforced by 4 longitudinal 50 mm diameter steel bars placed at each corner. If the column carries a comprehensive load of 300 kN, determine (i) Loads carried (ii) Stress produced in the concrete and Steel (08 Marks) bars.
 - A steel rod 15 m long at a temperature of 15°C. Find the free expansion of length when the temperature is raised to 65°C. Find the temperature stresses produced, when
 - The expansion of the rod is prevented.
 - The rod is permitted to expand by 6 mm.

Take $\alpha = 12 \times 10^{-6} / ^{\circ} \text{ C}$ and $E = 2 \times 10^{5} \text{ N/mm}^{2}$

(08 Marks)

Module-2

- The state of stress at a point in a strained material is shown in Fig. Q3. Determine 3
 - The direction of the principal planes.
 - The magnitude of principal stresses.
 - The magnitude of the maximum shear stress and its direction.
 - d) Draw Mohr's circle and verify the results obtained analytically.



(20 Marks)

L 1 JAN 2020



4 a. Differentiate between thin and thick cylinders.

(04 Marks)

- b. Derive an expression for circumferential stress and longitudinal stress for a thin cylinder subjected to an internal pressure 'P'. (06 Marks)
- c. A thick cylinder of 400 mm internal diameter and 100 mm thickness contains a fluid at a pressure 80 N/mm². Find hoop stresses across the section. Also sketch the radial and hoop stress distribution across the section. (10 Marks)

Module-3

Draw shear force and Bending Moment Diagrams for the beam shown in Fig. Q5. Locate the point of contraflexure. (20 Marks)





Fig. Q5

OR

6 a. Prove the relation $\frac{M}{I} = \frac{\sigma}{y} = \frac{E}{R}$ with usual notations.

(10 Marks)

b. The T-section of a beam is shown in Fig. Q6 (b). The material of the beam has yield strength of 250 MPa. Determine maximum moment of resistance that the beam can support if yielding is to be avoided. (10 Marks)



Note: All dimensions are in mm. Fig. Q6 (b)

Module-4

- a. A mild steel shaft 120 mm diameter is subjected to a maximum torque of 20×10^6 N-mm and a maximum bending moment of 12×10^6 N-mm at a particular section. Find the factor of safety (FoS) according to the maximum stress theory, if the elastic limit in simple tension is 220 N/mm^2 .
 - b. Prove that a hollow shaft is stronger and stiffer than the solid shaft of the same material, length and weight. (10 Marks)

