



10CV/CT52

**Fifth Semester B.E. Degree Examination, Aug./Sept.2020**  
**Design of RCC Structural Elements**

Max. Marks:100

- Note:** 1. Answer any FIVE full questions, selecting atleast TWO questions from each part.  
2. Use of IS:456-2000 and its design aid (SP-16) is permitted.  
3. Assume the missing data suitably.

**PART - A**

- 1 a. Explain in detail the necessity of considering partial safety factors in the limit state method of design. (05 Marks)  
b. Show that  $X_{u,max} = 0.46d$  for Fe500 grade steel. (05 Marks)  
c. Explain balanced section, under reinforced section and over reinforced section in limit state method of RCC design. (05 Marks)  
d. Show that  $P_{t,lim} = 41.4 \left( \frac{f_{ck}}{f_y} \right) \left( \frac{X_{u,max}}{d} \right)$ , with usual notations. (05 Marks)
- 2 a. A singly reinforced beam 250mm × 500mm in section is reinforced with 4 bars of 16mm diameter with an effective cover of 50mm. Find the ultimate moment of resistance of the beam. Use M20 concrete and Fe415 grade steel. (08 Marks)  
b. A doubly reinforced beam 250mm wide and 450mm deep to the centre of tensile reinforcement. It is reinforcement with 2#16φ as compression reinforcement at an effective cover of 50mm and 4#25φ as tensile steel. Using M15 concrete and Fe250 steel, calculate the ultimate moment of resistance of the beam section. (12 Marks)
- 3 a. Explain short term deflection and long term deflection. (04 Marks)  
b. What is development length? Obtain the expression for development length in tension. (06 Marks)  
c. A rectangular simply supported beam of span 5m is 300mm × 650mm in cross section and is reinforced with 3 bars of 20mm diameter on tension side at an effective cover of 50mm. Determine the short term deflection due to an imposed working load of 20 kN/m (Excluding self weight). Assume M20 concrete and Fe415 grade steel. (10 Marks)
- 4 A T-beam slab floor has 125mm thick slab forming part of T-beams which are of 8m clear span. The end bearings are 450mm thick. Spacing of T-beams is 3.5m. The live load on the floor is 3 kN/m<sup>2</sup>. Design one of the intermediate beams. Sketch the details of reinforcement. Use M20 concrete and Fe415 grade steel. (20 Marks)

**PART - B**

- 5 Design a R.C. slab for a room measuring 5m × 6m size. The slab is simply supported on all the four edges, with corners held down and carries a superimposed load of 3 kN/m<sup>2</sup> inclusive of floor finishes etc. Use M20 concrete and Fe415 steel. Adopt I.S. code method. (20 Marks)
- 6 a. Design a short axially loaded square column, 500mm × 500mm for a service load of 2000 kN. Use M20 concrete and Fe415 grade steel. (08 Marks)

- b. A column of size 300mm × 400mm has effective length of 3.6m and is subjected to  $P_u = 1100$  kN and  $M_u = 150$  kN-m about the major axis. Design the column using M25 concrete and Fe415 grade steel, providing the steel.

(i) On two sides

(ii) On four sides

Assume cover of 60mm.

CMRIT LIBRARY  
BANGALORE - 560 037

(12 Marks)

- 7 A rectangular column 400mm × 600mm carries a live load of 2000 kN. The safe bearing capacity of the soil is 150 kN/m<sup>2</sup>. Using M20 concrete and Fe415 steel, design a rectangular footing to support the column. Sketch the details of reinforcement. (20 Marks)

- 8 Design a dog legged stairs for an office building in a room measuring 2.8m × 5.8m clear. Vertical distance between the floors is 3.6m. Width of flight is to be 1.25m. Allow a live load of 3 kN/m<sup>2</sup>. Use M20 concrete and Fe415 steel. Assume the stairs are supported on 230mm walls at the end of outer edges of landing slabs. Sketch the details of reinforcement. (20 Marks)

\*\*\*\*\*