17EE554

(08 Marks)

(08 Marks)

(04 Marks)

(10 Marks)

(06 Marks)

(04 Marks)

(06 Marks)

(08 Marks)

(06 Marks)

(06 Marks)

(06 Marks)

(12 Marks)

(08 Marks)

CMRIT LIBRARY BANGALORE . 560 037

Max. Marks: 100

5

of the control scheme.

Discuss self control of permanent magnet synchronous motor. Also give the block diagram

Module-3

Explain the construction and operation of the synchronous reluctance motor.

OR

6	a.	Derive the emf equation of permanent magnet synchronous motor.	(10 Marks)
	b.	Draw the phasor diagram of synchronous reluctance motor.	(05 Marks)
	c.	Compare conventional and permanent magnet synchronous motor.	(05 Marks)

Module-4

7	a.	Derive the torque equations of single phase AC series motor.	(08 Marks)
	b.	Derive the transfer functions of field controlled DC servo motor.	(08 Marks)
	C.	List the characteristic features of repulsion motor.	(04 Marks)

OR

8	a.	Derive the torque equation of repulsion motor with two stator windings.	(08 Marks)
	b.	Derive the transfer function of armature controlled DC servomotor.	(08 Marks)
	c.	Give the circuit diagram of repulsion motor and draw its phasor diagram.	(04 Marks)

Module-5

- 9 a. Describe the following with respect to linear induction motors
 - i) transverse edge effect
 - ii) End effect

iii) entry and exit transients (08 Marks)

- b. Explain the constructions and operations of double sided brushless permanent magnet axial flux machine. (08 Marks)
- c. The secondary sheet of linear inductions motor having a pole pitch of 10cm move at a velocity 8 m/s. If the supply frequency is 50Hz, find the slip. (04 Marks)

OR

- 10 a. List the factors to be considered for the choice of
 - i) specific magnetic loading

ii) specific electric loading and explain

(10 Marks)

- b. With the help of a neat sketch, explain the construction of multi disc permanent magnet Axial flux machine. (06 Marks)
- c. A linear induction motor has a pole pitch of 5cm. It is supplied with 50Hz voltage. Find speeds of the field and runner, if the slip is 0.2. (04 Marks)

* * * *