

18EC53

Fifth Semester B.E. Degree Examination, Jan./Feb. 2021

Principles of Communication System

Time: 3 hrs.

BANGALOUE

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

- 1 a. Explain in detail the working of switching modulator with diagram and necessary derivations. (10 Marks)
 - b. Explain the generation of DSBSC modulated waves using ring modulator. (10 Marks)

OR

- 2 a. Illustrate the amplitude modulation process and draw the waveform for modulation index M > 1 & M < 1. (08 Marks)
 - b. Explain with relevant block diagram and working of FDM system. (08 Marks)
 - c. A 400 W carrier is modulated on a depth of 75 percent. Calculate the total power in the modulated wave of following form AM.
 - (i) Double Side Band with Full Carrier (DSBFC)
 - (ii) Double Side Band Suppressed Carrier (DSBSC)

(04 Marks)

Module-2

- 3 a. Derive the equations for frequency modulated wave. Define modulation index and frequency deviation.

 (12 Marks)
 - b. A 93.2 MHz carrier is frequency modulated by 5 kHz sine wave the resultant FM signal has frequency deviation of 40 kHz:
 - (i) Find the carrier swing of FM signal
 - (ii) What are highest and lowest frequencies of FM signal?
 - (iii) Calculate the modulation index of FM
 - (iv) B.W of FM signal

(08 Marks)

OR

- 4 a. Explain the Narrow band FM with relevant expressions and phasor diagrams. (10 Marks)
 - b. Discuss the nonlinear effects in FM system.

(06 Marks)

c. Assume that the maximum value of frequency deviation Δf is fixed at 50 kHz for a certain FM transmission. Given that the maximum modulating frequency is 15 kHz. Calculate the necessary transmission bandwidth. (04 Marks)

Module-3

- 5 a. Derive the expression for figure of merit for DSB-SC receiver. (10 Marks)
 - b. Find figure of merit for single tone FM.

(06 Marks)

- c. Write short notes on:
 - (i) Shot Noise
 - (ii) White Noise

(04 Marks)

OR

With FM receiver model, derive the expression for figure of merit. (10 Marks) Briefly explain the following as application to FM: Pre-emphasis (ii) De-emphasis (06 Marks) An AM receiver operating with a sinusoidal modulating signal has a following specifications: m = 0.8 and $(SNR)_0 = 30$ dB. What is carrier to noise ratio? (04 Marks) **Module-4** State sampling theorem and explain same with neat sketches and equation. (10 Marks) With neat block diagram, explain the TDM. (06 Marks) c. A Compact Disc (CD) audio signals digitally using PCM. Assume the audio signal bandwidth to be 20 kHz. What is the Nyquist rate? If the Nyquist samples are quantized to L = 65, 536 levels and then binary coded, determine the number of bits required to encode a sample. (04 Marks) 8 What are advantages digitizing the analog signals? (06 Marks) With a block diagram, explain the generation and detection of PPM. (10 Marks) c. Discuss Bandwidth - Noise trade off. (04 Marks) Module-5 With a neat diagram, explain the basic elements of a PCM. (08 Marks) b. Discuss the concept and operation of delta modulation in detail. (08 Marks) c. PCM system uses uniform quantizer followed by a 7 bit binary encoder. The bit rate of the system is 50×10^6 bps. What is minimum message bandwidth? (04 Marks) Write a note on MPEG + Video. 10 b. Draw the resulting waveform for 01101001 using unipolar NRZ, polar NRZ, unipolar Z2,

(10 Marks)

- Bipolar RZ. (06 Marks)
- c. A TV signal with a bandwidth of 4.2 MHz is transmitted using binary PCM. The number of representation level is 512. Calculate:
 - Codeword length
 - (ii) Final bit rate
 - (iii) Transmission bandwidth

(04 Marks)