With usual notations, show that the discharge through a venturimeter is given by

 $Q = C_d \frac{A_1 A_2}{\sqrt{A_1^2 - A_2^2}} \sqrt{2gh}.$ (06 Marks)

A pipeline carrying oil of specific gravity 0.9 changes in diameter from 20cm at a position A to 50cm at position B which is 5m at higher level. If the pressure at A and B are 10N/cm² and 6N/cm² respectively and discharge is 200litres/s, determine the loss of head and the direction of flow. (10 Marks)

o.

Module-3

- 5 a. Prove that the velocity distribution across the cross section of a circular pipe during viscous fluid flow is parabolic in nature. Also prove that the maximum velocity is in the centre of the pipe and is equal to twice the average velocity.

 (10 Marks)
 - b. Water at 15°C flows between two large parallel plates at a distance of 1.6mm apart. Determine: i) the maximum velocity ii) the pressure drop per unit length iii) the shear stress at the walls of the plates if the average velocity is 0.2m/s. The viscosity of water at 15°C is given as 0.01 poise.

 (06 Marks)

OR

- 6 a. Derive an expression for loss of head due to sudden enlargement of a pipe. (08 Marks)
 - b. An oil of specific gravity 0.9 and viscosity 0.06 poise is flowing through a pipe of diameter 200mm at the rate of 60 liters/s. Find the head loss due to friction for a 500m length of the pipe. Find the power required to maintain this flow. (08 Marks)

Module-4

- 7 a. Find the displacement thickness and the momentum thickness for the velocity distribution in the boundary layer given by $\frac{u}{U\infty} = \frac{y}{\delta}$, where u is the velocity at a distance y from the plate and $u = U_{\infty}$ and $y = \delta$, where δ = boundary layer thickness. Also calculate the ratio of displacement thickness to momentum thickness. (08 Marks)
 - b. Experiments were conducted in a wind tunnel with a wind speed of 50km/h on a flat plate 2m long and 1m wide. The density of air is 1.15kg/m³. The plate is kept at such an angle that the coefficient of lift and drag are 0.75 and 0.15 respectively. Determine:
 - i) lift force ii) drag force iii) resultant force iv) power exerted by air stream on the plate.
 (08 Marks)

OR

- 8 a. Explain the following terms:
 - i) Geometric similarity ii) Kinematic similarity iii) Dynamic similarity. (06 Marks)
 - b. A partially submerged body is towed in water. The resistance R to its motion depends on the density ρ , the viscosity μ of water, length ℓ of the body, velocity v of the body and the acceleration due to gravity g. By using Buckingham's π -theorem, show that the resistance to the motion can be expressed in the form

$$R = \rho \ell^2 v^2 \phi \left[\frac{\mu}{\rho v L}, \frac{\ell g}{v^2} \right]$$

(10 Marks)

Module-5

- a. From fundamentals, show that the velocity of a sound wave in a compressible fluid is given by $C = \sqrt{\frac{dp}{d\rho}}$. Further, show that this sonic velocity for an isentropic medium is given by
 - $c = \sqrt{rRT}$, where r = ratio of specific heats, R = Gas constant; T = Temperature.

(08 Marks)

- b. Define Mach number. Explain its significance in compressible flow. (04 Marks)
- c. Compute the velocity of a bullet fired in still air and Mach number when the mach angle is 30° . Take R = 0.28714kJ/kg K and r = 1.4. Assume air temperature to be 15° C. (04 Marks)

OR

- 10 a. Define and write the expression for: i) Stagnation enthalpy ii) Stagnation temperature iii) Stagnation pressure. (06 Marks)
 - b. Mention the advantages, disadvantages and limitation of CFD. (10 Marks)