CRASH COURSE

Seventh Semester B.E. Degree Examination, May 2017 Experimental Stress Analysis

Time: 3 hrs.

Max. Marks: 100

Note: Answer any FIVE full questions, selecting atleast TWO questions from each part.

PART - A

- a. What are the different types of adhesive used in strain gauges? Explain any two in brief.

 (06 Marks)
 - b. Define gauge factor. Explain with a neat sketch a Piezo-resistive strain gauge. (06 Marks)
 - Derive an expression for Potential difference across a constant current resistance bridge.

(08 Marks)

- 2 a. What do you understand by a strain rosette? What are the different types of strain rosette configuration currently in use? Discuss their uses and limitations. (08 Marks)
 - b. A delta rosette yields the following strain indications: $\epsilon_a = -845 \,\mu\text{m/m}$, $\epsilon_b = 1220 \,\mu\text{m/m}$ and $\epsilon_c = 710 \,\mu\text{m/m}$. Calcualte maximum principal strain direction, the principal stresses and the maximum shear stress, $E = 200 \,\text{GPa}$, V = 0.285.

(12 Marks)

- 3 a. With a neat sketch explain the elements of plane polariscope. (06 Marks)
 - b. Discuss the important properties of isoclinic's and isochromatic fringe pattern. (06 Marks)
 - c. Explain Calibration techniques used for photo elastic material. (08 Marks)
- 4 a. What are the important properties of an ideal photoelastic material? Discuss a few important photoelastic materials. (10 Marks)
 - b. Explain the different types of scaling model prototype for stress analysis in 2-D photo elasticity. (10 Marks)

PART - B

- 5 a. Define scattering. Explain the phenomenon associated with scattering property used as an polarizer and analiser. (10 Marks)
 - b. Describe briefly the scattered light method to photoelastic stress analysis. Discuss the advantages and limitations, of this method. (10 Marks)
- 6 a. What are the assumptions to be made to analyze the coating behaviour? Explain the reinforcing effects of a coating thickness applied to photoelastic materials. (10 Marks)
 - b. Explain the following stress separation techniques
 - i) Oblique incidence method ii) Strip coatings. (10 Marks)
- 7 a. Discuss the crack patterns in brittle coating obtained under various combinations of stresses.

 Illustrate your answer by giving sketches. (10 Marks)
 - b. Determine the stresses in a brittle coating applied to a component of steel for which $E_s = 200 GPA$, $V_s = 0.30$, when the specimen stresses are $\sigma_1^s = 210 \, MPa$ and $\sigma_2^s = -140 \, MPa$
 - i) For a resin based coating with $E_c = 1.40 \times 10^{-3}$ MPa and $V_c = 0.42$ and
 - ii) For a ceramic based coating with $E_c = 70 \times 10^3 MPa$ and $V_c = 0.25$.

If the threshold strain is 500μm/m, what is the corresponding state of stress in the coating during calibration? (10 Marks)

- 8 a. Explain the following Moire's Fringes analysis techniques
 - i) Geometrical approach ii) Displacement approach. (10 Marks)
 - b. Discuss the fundamental properties of the Moiré's Fringes. What conditions must be fulfilled for successful application of the Moiré's method. (10 Marks)

* * * * *