



15EC82

Eighth Semester B.E. Degree Examination, July/August 2022 **Fiber Optics and Networks**

MANGALONE Time: 3 hrs.

Max. Marks: 80

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

- a. Describe any five important advantages of optical fiber communication over other 1 communication.
 - b. A silica optical fiber with a core diameter large enough to be considered by ray theory analysis has a core refractive index of 1.50 and a cladding refractive index of 1.47. Determine
 - The critical angle at the core-cladding interface. (i)
 - The NA for the fiber. (ii)
 - (iii) The acceptance angle in air for the fiber.

(06 Marks)

OR

- With relevant diagrams, explain the different types of optical fibers, considering the refractive index profile, number of modes and material used.
 - b. A multimode step index fiber with a core diameter of 80 µm and a relative index difference of 1.5% is operating at a wavelength of 0.85 µm, If the core refractive index is 1.48, estimate:
 - The normalized frequency for the fiber; (i)
 - The number of guided modes. (ii)

(04 Marks)

Module-2

- Derive an expression for r.m.s pulse broadening due to intermodal dispersion in multimode 3 step index fiber. (08 Marks)
 - Explain different absorption mechanisms in optical fiber.

(08 Marks)

OR

Explain the different types of bending losses in optical fiber.

(06 Marks)

- b. A step index fiber has a core refractive index of 1.5 and a core diameter of 50 μm . The fiber is jointed with a lateral misalignment between the core axes of 5 µm. Estimate the insertion loss at the joint due to the lateral misalignment assuming a uniform distribution of power between all guided modes when:
 - There is a small air gap at the joint; (i)
 - The joint is considered index matched. (ii)

(06 Marks) (04 Marks)

c. Explain V-groove optical fiber splices technique.

CMRIT LIBRARY

BANGALORE - 560 037

Module-3

- Derive the expression for quantum efficiency and output power for an LED. (08 Marks)
 - Describe the different noise sources affecting the photo-detector along with appropriate (08 Marks) expressions.

OR

- 6 a. Starting from rate equations, derive the expression for the number of photons / unit volume resulting from stimulated and spontaneous emissions in LASER diode. (10 Marks)
 - b. Draw and explain two types of front-end amplifier used in optical fiber communication.

(06 Marks)

(06 Marks)

Module-4

a. Explain the operational principle and implementations of WDM with diagram. (08 Marks)
b. Describe the working principle of isolators and circulators with suitable diagram. (08 Marks)

OR

- 8 a. Draw the energy-level diagram indicating the transition processes in erubium doped silica fiber amplifier and explain the amplification mechanism. (06 Marks)
 - b. Based on general application, explain three types of optical amplifiers with relevant diagram. (10 Marks)

Module-5

- 9 a. Explain the different types of optical networking node elements. (10 Marks)
 - b. Explain ATM protocol architecture.

CMRIT LIBRARY
BANGALORE - 560 037

OR

a. Explain public telecommunications networks review with neat diagram.
b. Explain an optical packet switching network with neat diagram.
(06 Marks)

* * * * *