

CBCS SCHEME



USN

--	--	--	--	--	--	--	--	--	--

17ME53

Fifth Semester B.E. Degree Examination, Jan./Feb. 2023 Turbomachines

Max. Marks: 100

- Note: 1. Answer any FIVE full questions, choosing ONE full question from each module.
2. Use of Heat Transfer data handbook is permitted.*

Module-1

- 1 a. Define the following for turbomachine:
(i) Specific speed (ii) Flow coefficient
(iii) Energy coefficient (iv) Speed ratio (10 Marks)
- b. An output of 10 KW was recorded on a turbine, 0.5 diameter, revolving at a speed of 800 rpm, under a head of 20 m. What is the diameter and output of another turbine which works under a head of 180 m at a speed of 200 rpm when their efficiencies are same? Find the specific speed and name the turbine can be used. (10 Marks)

OR

- 2 a. Define polytropic efficiency of turbine. Show that the polytropic efficiency during expansion process is given by:

$$\eta_p = \frac{\ln \left[\frac{T_2}{T_1} \right]}{\frac{\gamma - 1}{\gamma} \ln \left[\frac{P_2}{P_1} \right]} \quad (10 \text{ Marks})$$

- b. A nine stage centrifugal compressor has an overall pressure ratio of 2.82. Air enters the compressor at a pressure of 1 bar and 17°C the stage efficiency is 0.9. Determine:
(i) Pre heat factor (ii) Overall efficiency (iii) Polytropic efficiency (10 Marks)

Module-2

- 3 a. Derive an expression for the alternative form of Euler's turbine equation. (10 Marks)
- b. Obtain an expression for utilization factor of a turbomachine interms of inlet and outlet absolute velocity of the fluid and degree of reaction. (10 Marks)

OR

- 4 a. Derive an expression for maximum utilization factor for axial flow type of impulse turbine and 50% reaction turbine. (10 Marks)
- b. Draw the inlet and outlet triangles for an axial flow compressor for which given :

- (i) Degree of reaction = 0.5
(ii) Inlet blade angle = 40°
(iii) Axial velocity of flow which is constant throughout = 125 m/s
(iv) RPM = 6500
(v) Radius 0.2 m

Calculate the power required in KW at an air flow rate of 15 kg/s. Find fluid angles at inlet and outlet. Assume blade speed is same at inlet and outlet. (10 Marks)

Module-3

- 5 a. Name the different compounding methods and explain any one. (10 Marks)
- b. A single stage impulse turbine has a diameter of 1.5 m and running at 3000 rpm. The nozzle angle is 20° , speed ratio is 0.45. Ratio of relative velocity at the outlet to that at inlet is 0.9. The outlet angle of the blade is 3° less than inlet angle. Steam flow rate is 6 kg/s. Draw the velocity triangles and find the following:
- (i) Velocity of whirl (ii) Axial thrust
(iii) Blade angles (iv) Power developed (10 Marks)

OR

- 6 a. Explain the following:
- (i) Nozzle efficiency (ii) Diagram efficiency
(iii) Stage efficiency (iv) Axial thrust (10 Marks)
- b. Derive an expression for maximum blade efficiency in an impulse steam turbine. (10 Marks)

Module-4

- 7 a. Show that for maximum utilization the speed ratio is 0.5 for pelton wheel. (10 Marks)
- b. Define the following with reference to hydraulic turbines:
- (i) Overall efficiency (ii) Hydraulic efficiency
(iii) Mechanical efficiency (iv) Volumetric efficiency (10 Marks)

OR

- 8 a. Draw a neat sketch of Francis turbine. Explain different types of draft tube. Draw typical velocity triangles for Francis turbine. (10 Marks)
- b. A double jet pelton wheel is required to generate 7500 KW under a head of 400 m. The deflection of jet is 165° and the relative velocity of the jet is reduced by 15% in passing over the buckets. Find:
- (i) The diameter of each jet
(ii) Total flow
(iii) Force exerted by the jets in the tangential direction.
Assume generator efficiency is 95%, $\eta_0 = 80\%$, speed ratio = 0.47. (10 Marks)

Module-5

- 9 a. Explain the following with reference to centrifugal pump:
- (i) Manometric efficiency (ii) Cavitation (iii) Need of priming
(iv) Pumps in series (v) Mechanical efficiency (10 Marks)
- b. Derive an expression of pressure rise in the impeller of centrifugal pump. (10 Marks)

OR

- 10 a. Define the following:
- (i) Pre whirl (ii) Surging (iii) Slip factor (iv) Choking (10 Marks)
- b. An air compressor has eight stages of equal pressure ratio of 1.35. The flow rate and overall efficiency are 50 kg/s and 82% respectively if the conditions of air at entry are 1 bar and 40°C , determine:
- (i) The state of air at the compressor exit
(ii) Polytropic efficiency
(iii) Efficiency of each stage (10 Marks)
